



Fully automatic pocket spring assembler



FPA-300

- Processes up to 12 cycles per minute
- Highly flexible and fast setup and conversion to different pocket spring dimensions
- Variable assembly system for „top/bottom“ and/or „center“ gluing
- Fully automatic production of zoned spring units
- Assembly types: longitudinal, lateral, parallel, nested and duplex
- Freely programmable glue saving system with interrupted gluing lines
- Allows online helpdesk support
- Easy access to all components of the machine for maintenance and cleaning
- Integrated output table for spring units
- Smart Services
 - Spühl Monitoring & Analytics
 - Spühl Connect
 - Spühl Schedule

FPA-300



Working range

TECHNICAL DATA OF THE FPA-300 AT A GLANCE

Type of springs	Barrel / Cylindrical
Spring dimensions	Outer waist diameter Ø (Dta) 40 - 80 mm Pocket spring unit width: max. 2'100 mm
Spring height in pocket	70 - 230 mm
Performance	up to 12 cycles / minute
Air consumption	approx. 10 m ³ / hour
Air pressure required	6 bar
Power consumption total	approx. 10 kVA, after 20min heating time 6kVA
Power requirements	Operating Voltage: 3 x 400 V Frequency: 50 / 60 Hz Pre-fuse: 40 A Cable cross section: 4 x 10mm ²
Working temperature	+10° C to +40° C
Weight	net approx. 5'650 kg (Machine feeding unit net. approx. 200 kg each)
Space requirements	Details and machine layout please visit: www.spuhl.com

CE The machine complies with CE safety standards

Subject to changes without notice. The machine will be set for one spring type only from its working range. Each additional modification of the actual coil specification(Dta, wire ø, turns, height etc.) may request additional tools.

FIDES
a spühl brand

Spühl GmbH
Grüntalstrasse 23
9300 Wittenbach
Switzerland

Phone +41 71 292 13 12
saleswfm@spuhl.com
www.spuhl.com



Certified Management System according to
ISO 9001 and ISO 14001